

# SKYVAC INDUSTRIAL

## EXCLUSIVE CHARACTERISTICS

- ▶ INNOVATIVE GASKET
- ▶ INDEPENDENT MOTORS WITH LIGHT SWITCHES
- ▶ SEALANT FLOATER & INTEGRATED ANTIFOAM SYSTEM
- ▶ TIPPING TROLLEY
- ▶ RELIABLE CONSTRUCTION FOR INTENSIVE USE
- ▶ DETACHABLE TANK AND SOLID CART
- ▶ METAL TANGENTIAL INLET
- ▶ BIG WHEELS WITH BRAKES



## TECHNICAL DATA

**KS2/78 SKYVAC INDUSTRIAL**  
ASDO15555

Code		
PERFORMANCE		
Usage		WET & DRY
Motor		2x1 stage
Power	W	2000-2400 max
Voltage	V	220-240
Water lift	mmH2O	2470 FM OFF 3800 FM ON
Airflow	m3/h	420 FM OFF 220 FM ON
Tank Capacity/Material	l	78/steel
Cable length	m	8,5
Sound Pressure Level (EN 60704-1; EN 60704-2-1; IEC 60335-2-69)	dB(A)	74
Diameter of flexible hose	mm	50
Dimensions (LxWxH)	mm	700x580 X1100
Weight	kg	42

## SPECS



SOLID CART WITH TIPPING TANK



FLOWMIX



CARTRIDGE PROTECTION